



This submittal sheet is intended to be read in conjunction with the Allura Installation Manual dated January 2025. If a more current version of the Installation Manual or this submittal sheet is available, this version is no longer applicable.

### SUBMITTAL FORM

Submitted to	
Project Name	
Submitted by	
Date	
Additional Notes	

Note: Not all sizes and finishes are available in all markets. Contact your Allura representative or Allura Customer Experience for product and market availability.

## Allura Soffit

**DIVISION: 07 00 00 THERMAL AND MOISTURE PROTECTION**

**SECTION: 07 46 46 FIBER-CEMENT SIDING**

### MANUFACTURER

**Plycem USA, LLC, dba Allura**

The products are manufactured at the follow locations, with quality control inspections by QAI Laboratories.

- White City, Oregon
- Nuevo Laredo, Mexico
- Roaring River, North Carolina

### COMPLIES WITH THE FOLLOWING CODES

- 2018, 2015 International Building Code (IBC)
- 2018, 2015 International Residential Code (IRC)
- 2019, 2016 California Green building Standards Code (CalGreen), Title 24 Part 11
- 2020/2015 ICC 700 National Green Building Standards™ (ICC 700)

### PRODUCT SUBMITTED

**Product Size:**  12" X 12'  16" X 12'  24" X 12'

**Product Ventilation:**  Vented  Unvented

**Product Finish:**

Primed  Allura Spectrum®  The Wood Series™

**Product Texture:**  Smooth  Traditional

### FEATURES



Engineered to endure impact, harsh weather, including wind, thermal cycling, rain, humidity, and UV radiation.



Resists termite attack, pests, and rot.



NFPA Class A Fire Rating, Ignition Resistant Material and Noncombustible Material.



FEMA Class 5 Flood Damage-Resistant Material.

### USE

Allura Soffit is used as exterior soffit covering of buildings. Allura Vented Soffit has a net free air space of 6.9 in<sup>2</sup> per lineal foot.

### WARRANTY

Allura Siding: 30-Year Transferable, Non-Prorated, Limited Warranty

Allura Spectrum: 15-Year, Transferrable Limited Finish Warranty

This Submittal Sheet is provided for informational purposes and intended as a guideline and is not intended to be a warranty or promise as to product performance. Please refer to Allura's applicable written installation instructions and Limited Warranties for more information. Please comply with applicable building codes effective in the city, state, or town where the installation is occurring. In the event there are discrepancies between Allura's installation instruction and applicable building code, adhere to the requirement that is more stringent. Failure to do so may violate laws, affect product performance, result in personal injury, and may affect warranty coverage. Compliance with local building codes, regulations, and standards is the responsibility of the installer. Any information or assistance provided by Allura in relation to specific projects must be approved by the relevant specialists engaged for the project eg. builder, architect, or engineer.





## DESCRIPTION

Allura Soffit is a single faced, cellulose fiber-reinforced cement (fiber-cement) product. Allura Soffit has a flame spread index of 0 and a smoke developed index of  $\leq 5$  when evaluated in accordance with ASTM E84. Allura Soffit is classified as non-combustible when evaluated in accordance with ASTM E136 and CAN/ULC S114.

## AVAILABLE SIZES

WIDTH	LENGTH	THICKNESS
12" (305mm)		
16" (406mm)	12-feet (1,219mm)	¼" (6.4mm)
24" (610mm)		

## TEXTURE & FINISH

Allura Soffit is available in smooth and traditional (wood-grain) textures. Allura Soffit may be primed for field finishing, or factory-finished with Allura Spectrum®.

## INSTALLATION

Install Allura Soffit in accordance with:

- Allura Printed installation instructions
- QAI Laboratories CERus-1012
- Requirements of authorities having jurisdiction

## STORAGE AND HANDLING

Allura Soffit must be covered, and stored off the ground, on a clean, flat, and level surface. Keep Soffit dry during storage. See Allura Installation Manual for additional information.

## PERFORMANCE CHARACTERISTICS & CERTIFICATIONS

### PHYSICAL AND DURABILITY CHARACTERISTICS

- Allura Soffit complies with ASTM C1186, Type A, Grade II when tested and evaluated in accordance with ASTM C1185.

### FIRE CHARACTERISTICS

- Allura Soffit has a flame spread index of 0 and a smoke developed index of  $\leq 5$  when tested and evaluated in accordance with ASTM E84 (extended 20-minutes), and ASTM E2768.
- Allura Soffit is classified as non-combustible when evaluated in accordance with ASTM E136 and CAN/ULC S114.

### ADDITIONAL CERTIFICATIONS

- Miami-Dade County, Product Control Section Notice of Acceptance (NOA) 24-0408-04
- Texas Department of Insurance (TDI) listing EC-16

## ADDITIONAL RESOURCES

For additional resources, including our most current installation instructions and code reports, please visit our website at [www.allurausa.com](http://www.allurausa.com). For technical services email [technical.services@elementia.com](mailto:technical.services@elementia.com) or call 844.4.ALLURA.

This Submittal Sheet is provided for informational purposes and intended as a guideline and is not intended to be a warranty or promise as to product performance. Please refer to Allura's applicable written installation instructions and Limited Warranties for more information. Please comply with applicable building codes effective in the city, state, or town where the installation is occurring. In the event there are discrepancies between Allura's installation instruction and applicable building code, adhere to the requirement that is more stringent. Failure to do so may violate laws, affect product performance, result in personal injury, and may affect warranty coverage. Compliance with local building codes, regulations, and standards is the responsibility of the installer. Any information or assistance provided by Allura in relation to specific projects must be approved by the relevant specialists engaged for the project eg, builder, architect, or engineer.