



This submittal sheet is intended to be read in conjunction with the Allura Installation Manual dated January 2025. If a more current version of the Installation Manual or this submittal sheet is available, this version is no longer applicable.

## SUBMITTAL FORM

Submitted to	
Project Name	
Submitted by	
Date	
Additional Notes	

Note: Not all sizes and finishes are available in all markets. Contact your Allura representative or Allura Customer Experience for product and market availability.

## PRODUCT SUBMITTED

## Product Size:

- 7/16" X 4"   
  7/16" X 6"   
  7/16" X 8"   
  7/16" X 12"
- 4/4 X 2"   
  4/4 X 3"   
  4/4 X 4"   
  4/4 X 6"
- 4/4 X 8"   
  4/4 X 10"   
  4/4 X 12"
- 5/4 X 2"   
  5/4 X 3"   
  5/4 X 4"   
  5/4 X 6"
- 5/4 X 8"   
  5/4 X 10"   
  5/4 X 12"
- 8/4 X 2"   
  8/4 X 4"   
  8/4 X 6"

## Product Finish:

- Primed   
  Allura Spectrum®

## FEATURES



Engineered to endure impact, harsh weather, including wind, thermal cycling, rain, humidity, and UV radiation.



Resists termite attack, pests, and rot.



NFPA Class A Fire Rating, Ignition Resistant Material and Noncombustible Material.



FEMA Class 5 Flood Damage-Resistant Material

This Submittal Sheet is provided for informational purposes and intended as a guideline and is not intended to be a warranty or promise as to product performance. Please refer to Allura's applicable written installation instructions and Limited Warranties for more information. Please comply with applicable building codes effective in the city, state, or town where the installation is occurring. In the event there are discrepancies between Allura's installation instruction and applicable building code, adhere to the requirement that is more stringent. Failure to do so may violate laws, affect product performance, result in personal injury, and may affect warranty coverage. Compliance with local building codes, regulations, and standards is the responsibility of the installer. Any information or assistance provided by Allura in relation to specific projects must be approved by the relevant specialists engaged for the project eg, builder, architect, or engineer.



## Allura Reversible Trim

DIVISION: 07 00 00 THERMAL AND MOISTURE PROTECTION

SECTION: 07 46 46 FIBER-CEMENT SIDING

### MANUFACTURER

Plycem Construsistemas, dba Allura

### USE

Allura Reversible Trim is used as exterior decorative trim for use around windows, doors, facia and other architectural accents.

### INSTALLATION

Install Allura Reversible Trim in accordance with:

- Allura printed installation instructions
- QAI Laboratories CERus-1012
- Requirements of authorities having jurisdiction

### DESCRIPTION

Allura Reversible Trim is a cellulose fiber-reinforced cement (fiber-cement) product. Allura Reversible Trim has a flame spread index of 0 and a smoke developed index of  $\leq 5$  when evaluated in accordance with ASTM E84.

### TEXTURE & FINISH

Allura Reversible Trim is manufactured with one side smooth textured and the opposite side in traditional (wood-grain) texture. Allura Reversible Trim may be primed for field finishing, or factory-finished with Allura Spectrum®.

### ADDITIONAL RESOURCES

For additional resources, including our most current installation instructions and code reports, please visit our website at [www.allurausa.com](http://www.allurausa.com). For technical services email [technical.services@elementia.com](mailto:technical.services@elementia.com) or call 844.4.ALLURA.

### STORAGE AND HANDLING

Allura Reversible Trim must be covered, and stored off the ground, on a clean, flat, and level surface. Keep Trim dry during storage. See Allura Installation Manual for additional information.

### WARRANTY

Allura Trim: 15-Year Transferable, Limited Warranty

Allura Spectrum: 15-Year, Transferrable Limited Finish Warranty

This Submittal Sheet is provided for informational purposes and intended as a guideline and is not intended to be a warranty or promise as to product performance. Please refer to Allura's applicable written installation instructions and Limited Warranties for more information. Please comply with applicable building codes effective in the city, state, or town where the installation is occurring. In the event there are discrepancies between Allura's installation instruction and applicable building code, adhere to the requirement that is more stringent. Failure to do so may violate laws, affect product performance, result in personal injury, and may affect warranty coverage. Compliance with local building codes, regulations, and standards is the responsibility of the installer. Any information or assistance provided by Allura in relation to specific projects must be approved by the relevant specialists engaged for the project eg, builder, architect, or engineer.





## AVAILABLE SIZES

## REVERSIBLE TRIM—7/16" THICK

Product	Nominal Thickness	Nominal Width	Length	Actual Thickness	Actual Width
7/16X4	7/16" (11.1mm)	4" (101.6mm)	12' (3658mm)	7/16" (11.1mm)	3-1/2" (85.8mm)
7/16X6	7/16" (11.1mm)	6" (152.4mm)	12' (3658mm)	7/16" (11.1mm)	5-1/2" (134.8mm)
7/16X8	7/16" (11.1mm)	8" (203.2mm)	12' (3658mm)	7/16" (11.1mm)	7-1/4" (177.6mm)
7/16X12	7/16" (11.1mm)	12" (308.8mm)	12' (3658mm)	7/16" (11.1mm)	11-1/4" (275.6mm)

## REVERSIBLE TRIM—4 QUARTER (4/4)

Product	Nominal Thickness	Nominal Width	Length	Actual Thickness	Actual Width
4/4X2	1" (25.4mm)	2" (50.8mm)	12' (3658mm)	3/4" (19.1mm)	1-3/4" (44.5mm)
4/4X3	1" (25.4mm)	3" (76.2mm)	12' (3658mm)	3/4" (19.1mm)	2-1/2" (63.5mm)
4/4X4	1" (25.4mm)	4" (101.6mm)	12' (3658mm)	3/4" (19.1mm)	3-1/2" (85.8mm)
4/4X6	1" (25.4mm)	6" (152.4mm)	12' (3658mm)	3/4" (19.1mm)	5-1/2" (134.8mm)
4/4X8	1" (25.4mm)	8" (203.2mm)	12' (3658mm)	3/4" (19.1mm)	7-1/4" (177.6mm)
4/4X10	1" (25.4mm)	10" (254.0mm)	12' (3658mm)	3/4" (19.1mm)	9-1/4" (226.6mm)
4/4X12	1" (25.4mm)	12" (308.8mm)	12' (3658mm)	3/4" (19.1mm)	11-1/4" (275.6mm)

## REVERSIBLE TRIM—5 QUARTER (5/4)

Product	Nominal Thickness	Nominal Width	Length	Actual Thickness	Actual Width
5/4X2	1-1/4" (31.8mm)	2" (50.8mm)	12' (3658mm)	1" (25.4mm)	1-3/4" (44.5mm)
5/4X3	1-1/4" (31.8mm)	3" (76.2mm)	12' (3658mm)	1" (25.4mm)	2-1/2" (63.5mm)
5/4X4	1-1/4" (31.8mm)	4" (101.6mm)	12' (3658mm)	1" (25.4mm)	3-1/2" (85.8mm)
5/4X5	1-1/4" (31.8mm)	5" (127.0mm)	12' (3658mm)	1" (25.4mm)	4-1/2" (110.3mm)
5/4X6	1-1/4" (31.8mm)	6" (152.4mm)	12' (3658mm)	1" (25.4mm)	5-1/2" (134.8mm)
5/4X8	1-1/4" (31.8mm)	8" (203.2mm)	12' (3658mm)	1" (25.4mm)	7-1/4" (177.6mm)
5/4X10	1-1/4" (31.8mm)	10" (254.0mm)	12' (3658mm)	1" (25.4mm)	9-1/4" (226.6mm)
5/4X12	1-1/4" (31.8mm)	12" (308.8mm)	12' (3658mm)	1" (25.4mm)	11-1/4" (275.6mm)

## REVERSIBLE TRIM—8 QUARTER (8/4)

Product	Nominal Thickness	Nominal Width	Length	Actual Thickness	Actual Width
8/4X2	2" (50.8mm)	2" (50.8mm)	12' (3658mm)	1-1/2" (38.1mm)	1-3/4" (44.5mm)
8/4X4	2" (50.8mm)	4" (101.6mm)	12' (3658mm)	1-1/2" (38.1mm)	3-1/2" (85.8mm)
8/4X6	2" (50.8mm)	6" (152.4mm)	12' (3658mm)	1-1/2" (38.1mm)	5-1/2" (134.8mm)

This Submittal Sheet is provided for informational purposes and intended as a guideline and is not intended to be a warranty or promise as to product performance. Please refer to Allura's applicable written installation instructions and Limited Warranties for more information. Please comply with applicable building codes effective in the city, state, or town where the installation is occurring. In the event there are discrepancies between Allura's installation instruction and applicable building code, adhere to the requirement that is more stringent. Failure to do so may violate laws, affect product performance, result in personal injury, and may affect warranty coverage. Compliance with local building codes, regulations, and standards is the responsibility of the installer. Any information or assistance provided by Allura in relation to specific projects must be approved by the relevant specialists engaged for the project eg. builder, architect, or engineer.

